

USG RADAR™ BASIC ACOUSTICAL PANELS

USG Radar™ Basic Acoustical
Panels with USG Donn® Brand DX®
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Nondirectional pattern with a fresh, clean appearance offers fast, efficient installation.
- Economical, all-purpose ceiling pattern offered in many sizes.
- Optional Firecode® product designed to meet life-safety codes.
- USDA Certified Biobased Product.⁸

APPLICATIONS

- Schools
- Corridors
- Offices
- Retail stores

SUBSTRATE

- Wet-formed mineral fiber

Lightly Textured Panel

USG RADAR™ BASIC ACOUSTICAL PANELS

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818



YEAR
AVAILABILITY
2110, 2120, 2310, 2742



HIGH RECYCLED
CONTENT



UL Classified

Edge	Panel Size Imperial Metric (mm)	Fire Rating ²	Item No. Imperial Metric (mm)	NRC	CAC Min.	LR ³	Color ⁶	Grid Options	VOC Emissions	Recycled Content ¹	Panel Cost
SQ 	2'x2'x5/8" 600x600x15	Class A	2110 ME2110	0.55	33	0.83	White	A,C	Low	24-25%	\$
	2'x2'x5/8"		2115	0.55	35	0.83	White	B	Low	48- 49%	\$
	2'x4'x5/8" 600x1200x15	Class A	2310 ME2310	0.55	35	0.83	White	A,C	Low	24-25%	\$
	2'x4'x5/8"		2315	0.55	35	0.83	White	B	Low	48- 49%	\$
	2'x5'x5/8"	Class A	2619	0.55	35	0.83	White	A,C	Low	24-25%	\$
	20"x60"x5/8" 500x1500x15	Class A	2617 ME2617	0.55	35	0.83	White	A,C	Low	24-25%	\$
	30"x60"x3/4"	Class A	2618	0.60	35	0.83	White	A,C	Low	24-25%	\$
SLT 	2'x2'x5/8" 600x600x15	Class A	2120 ME2120	0.55	33	0.83	White	D	Low	24-25%	\$
	2'x2'x5/8"		2125	0.55	35	0.83	White	E	Low	48-59%	\$
	2'x4'x5/8"	Class A	2320	0.55	35	0.83	White	D	Low	24-25%	\$
	20"x60"x5/8"	Class A	2627	0.55	35	0.83	White	D	Low	24-25%	\$
FLB 	2'x2'x5/8"	Class A	2130	0.55	33	0.83	White	F,G,H,I	Low	24-25%	\$
BESK 	12"x12"x5/8"	Class A	2990	0.50	40	0.83	White	J	Low	44%	\$\$\$
SLT 	2'x4'x3/4"	Class A	2742	0.55	35	0.83	White	D	Low	26-27%	\$

USG RADAR™
BASIC PANEL

USG RADAR™ BASIC TILE^{4,5}

USG RADAR™ ILLUSION
BASIC TWO/24 PANEL

PATTERNS

Illusion™ Two/24



The look of 2'x2' panels

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

Firecode®



GRID PROFILE OPTIONS

A USG DX®	B USG DXL™	C USG DXW™	D USG DX®	E USG DXL™	F USG Centricitee™ DXT™	G USG Fineline® DXF™	H USG Fineline® 1/8 DXFF™	I USG Identitee® DXI™	J USG DX® Concealed

PHYSICAL DATA/
FOOTNOTES

Product literature
Data sheet: SC2288

ASTM E1264 classification
Type III, Form 2, Pattern C, E
and C, E, K

ASTM E84 and CAN/ULC S102
surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

UL Type
FR-83

Weight
0.61-1.15 lb./sq. ft.

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance
R-1.4 (Class A, 5/8" panels and tile)
R-1.7 (Class A, 3/4" panels)
R-1.4 (Class A, 15 mm panels)
R-1.6 (Firecode®, 5/8" panels)

Maximum backloading
See USG 30-Year Limited System Warranty Commercial
Applications (SC2102).

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Metric sizes available
Contact sales for minimum quantities and lead times.

Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- Fire-rated items: see UL design details.
- LR values are shown as averages.
- Contact USG for adhesive recommendation for 12"x12" glue-up applications.
- Not UL Classified for acoustics.
- No Flat Black or 'Deeptones' are available on any reveal edge or USG Radar™ Firecode® panel.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

Notice
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2288/rev. 2-23
© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, FIRECODE, IDENTITEE, RADAR, IT'S YOUR WORLD, BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

